

552,910

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099054 A1

(51) International Patent Classification⁷: B66B 1/34, 7/04

(21) International Application Number:

PCT/US2003/011596

(22) International Filing Date: 15 April 2003 (15.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant: OTIS ELEVATOR COMPANY [US/US];
Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): KULAK, Richard
[US/US]; 80 Aldbourne Drive, Bristol, CT 06010 (US).
TRACEY, Michael [US/US]; 637 Main Street, Cromwell,
CT 06416 (US).

(74) Agent: SIRAGUSA, John, M.; Carlson, Gaskey & Olds,
400 West Maple Road, Suite 350, Birmingham, MI 48009
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (*Rule 4.17(iv)*) *for US only*

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELEVATOR WITH ROLLERS HAVING SELECTIVELY VARIABLE HARDNESS



(57) Abstract: An elevator system includes a roller (16) having a hardness that varies responsive to a magnetic field (20). The roller (16) rolls along a guide rail (28) to maintain a desired orientation of the elevator car (12). In one example, the roller (16) includes a membrane (30) defining a generally annular chamber (36) containing fluid (22) that changes viscosity responsive to changes in the magnetic field (20). The rollers (16) are associated with at least one magnetic field generator (18) that generates a magnetic field (20) of a selected strength. Varying the magnetic field varies the hardness of each roller (16) to control vibrations of the elevator car (12) to improve ride quality.

WO 2004/099054 A1